




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>6</sup> : <b>G09G 3/36, G06F 3/147, H04N 5/44, 5/907</b>		<b>A1</b>	(11) International Publication Number: <b>WO 95/09412</b>
			(43) International Publication Date: <b>6 April 1995 (06.04.95)</b>
(21) International Application Number: <b>PCT/US94/09475</b>		(81) Designated States: CA, JP, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).	
(22) International Filing Date: <b>24 August 1994 (24.08.94)</b>		<b>Published</b> <i>With international search report.</i>	
(30) Priority Data: <b>08/127,565</b> <b>27 September 1993 (27.09.93)</b> <b>US</b>			
(71) Applicant: <b>HONEYWELL INC. [US/US]; Honeywell Plaza, Minneapolis, MN 55408 (US).</b>			
(72) Inventors: <b>MILLER, David, W.; 2540 Sunset Drive #147, Longmont, CO 80501 (US). NELSON, Larry, A.; 15930 Northeast 6th Street, Bellevue, WA 98008 (US). ROBINDER, Ronald, C.; 10312 Trevino Loop Northwest, Albuquerque, NM 87114-4942 (US).</b>			
(74) Agent: <b>JOHNSON, Kenneth, J.; Honeywell Inc., Honeywell Plaza - MN12-8251, Minneapolis, MN 55408 (US).</b>			

## (54) Title: SIMPLIFIED IMAGE RECONSTRUCTION INTERFACE



## (57) Abstract

A video interface apparatus for converting an incoming interlaced video signal to an outgoing non-interlaced video signal for an LCD flat panel with an arbitrary number of rows and columns. The incoming video signal is digitized (101) and stored in a memory (103). An address generator (105) creates addresses for reading and writing data from and into the memory, and the resulting read data is used to reconstruct the digital signal into an image for display of the LCD flat panel (107).

BEST AVAILABLE COPY

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

-1-

## SIMPLIFIED IMAGE RECONSTRUCTION INTERFACE

### FIELD OF THE INVENTION

The present invention pertains generally to a device for displaying a picture, and more particularly to an electronic interface for converting an interlaced video signal to a liquid-crystal display (LCD) flat panel with an arbitrary number of rows and columns.

### BACKGROUND OF THE INVENTION

Flat panel displays, and particularly LCD panels, have generally been fabricated in the past such that there is a 1:1 correspondence between the display surface geometry and the image pixel geometry. This leads to very high data rates for LCD panels that have many pixels and display a wide number of grey scale levels. With these display systems, any improvements in imaging or in panel production capability require a redesign of the entire display system.

Conversely, cathode ray tube (CRT) displays have used a well-defined series of interface standards, such as the Electronic Industries Association (EIA) RS-170 and RS-343 standards, to support displays of varying sizes and with varying performance tradeoffs. Previously disclosed flat panel LCD interfaces have required high speed video data processing in order to scan the image onto LCD panels of varying sizes and pixel counts. Such interfaces also require scanning video information onto an LCD flat panel using a non-interlaced standard with a refresh rate that is high enough to be above the flicker fusion frequency of the human eye.

Therefore, there is a need for a video interface to convert an incoming interlaced video signal to an outgoing non-interlaced video signal for an LCD flat panel with an arbitrary number of rows and columns.

### SUMMARY OF THE INVENTION

The present invention provides a video interface apparatus for converting an incoming interlaced video signal to an outgoing non-interlaced video signal for an LCD flat panel with an arbitrary number of rows and columns. The incoming video signal is digitized and stored in a memory. An address generator creates addresses for reading and writing data from and into the memory, and the resulting read data is used to reconstruct the digital signal into an image for display on the LCD flat panel.

### BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a block diagram showing an electronic video interface compatible with the present invention.

Fig. 2 is a block diagram showing an image reconstruction engine compatible with the present invention.

Fig. 3 is a block diagram showing an image rotation compatible with the present invention.

### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

In the following detailed description of the preferred embodiments, reference is made to the accompanying drawings which form a part hereof, and in which is shown by way of illustration specific embodiments in which the invention may be practiced. It is to be understood that other embodiments may be utilized and structural changes may be made without departing from the scope of the present invention.

For the purpose of this description, it is assumed that the described components, timings, frequencies and signals are compatible with those required to convert a standard RS-170 video signal for display on an LCD flat panel with a resolution of 1024 x 1024 pixels. However, it will be recognized that the present invention is not limited to the preferred embodiment described below and may be readily adapted to other video signals, either color or monochrome, and flat panel display resolutions, either greater than or less than the incoming video signal, without loss of generality.

A typical video signal input converted by the present invention is described in the published Electronic Industries Association (EIA) RS-170 document, which describes the video signal standard currently used by the civilian television broadcast industry. The RS-170 video signal provides for 525 horizontal scan lines, a 2:1 interlace, a 30 Hz frame rate, and a 1.0 volt peak luminance level. Although not specifically defined in the published EIA specification, data in an RS-170 video signal is generally considered to be bandwidth limited to substantially 4.5 MHz. A color RS-170 video signal as currently used by the broadcast industry has three signal elements: red, green with composite synchronization, and blue.

In a particular instance of interest to the assignee of the present invention, Honeywell Inc., the input video signal comprises a modified RS-170 video signal where the signal levels are 2.4 volts peak luminance level, rather than the 1.0 volts of the

RS-170 video standard, and the bandwidth is limited between 8 and 9 MHz. Bandwidth limiting is required in order to display a 484 x 484 point preferred digital map output with reasonable fidelity. The preferred embodiment of the present invention is designed to accommodate either the modified RS-170 video signal voltage level of 2.4 volts or  
5 the standard RS-170 video signal voltage level of 1.0 volts by means of a resistor pack or a switch.

The LCD flat panel display module of the preferred embodiment is manufactured by Honeywell Inc., and requires 1024 digital words of memory (each word is 8 bits wide) per horizontal scan line to store the LCD flat panel driver signal data, with 7 bits specifying the intensity of the signal and the last bit serving to identify  
10 drive polarity. This reversal of drive polarity is necessary for an LCD flat panel display to prevent damage to the panel. Row (source) drivers output video data to the horizontal scan lines of the LCD flat panel display, with the output voltage being at a negative power supply rail for a minimum input data value of 0 and at a positive power supply  
15 rail for a maximum input data value of 255. Consequently, the LCD flat panel driver signal data must be complemented periodically. As the LCD flat panel display has a response of input voltage to display contrast which is highly non-linear, a 5-to-8 bit look-up table is used to convert an incoming RS-170 video signal to an appropriate LCD flat panel driver signal.

20 The LCD flat panel of the preferred embodiment has 1024 horizontal scan lines to be provided with information, and the panel is mounted orthogonally (rotated by 90°) to the usual orientation of a panel, as shown in Fig. 3. Due to the orthogonal mounting and an RGB triad dot structure to provide color, the horizontal rows of dots are staggered by 0.5 pixels. The LCD flat panel driver data is formatted into 16 channels of  
25 64 horizontal rows for display on the panel. The data is applied to the row drivers, and a column is selected by corresponding column drivers.

The LCD flat panel display module of the preferred embodiment uses five basic clocks: 1) a reset pulse for the row drivers, 2) a four-phase clock operating at approximately 1 MHz, 3) first and second output signals, 4) a seed pulse (GD) for the  
30 column drivers, and 5) a shift clock (YSCL) for the column drivers.

Fig. 1 shows a typical scan conversion and image rotation interface. The composite synchronization signals of the green channel are stripped from the input

video signal, and the horizontal and vertical synchronization pulses are used to keep a phase-locked-loop operating in proper phase to provide the required clocks. The clocks range from a 64 MHz data output clock to a 30 Hz output selection clock. A reset pulse for the row drivers is required which may be once per frame or once upon start-up of the display head.

After the synchronization has been stripped off the green channel, the three RGB channels are identical so the data manipulations for all three channels are handled in the same way. The description that follows is for each single color plane. Each block of the circuit is typically duplicated in triplicate in the interface unless specifically stated otherwise.

The RS-170 video input signal is first low-pass filtered to substantially 4.6 MHz. The filtering is typically used to minimize the introduction of aliasing effects during subsequent sampling and reconstruction steps. The input signal normally consists of 484 data points per horizontal scan line, and therefore a bright to dark to bright (or the converse) input signal represents a spatial frequency of 242 cycles per screen width. To convert this to bandwidth in the time domain, the number of cycles per scan line is divided by the time available to reproduce the scan line, which is approximately 52.5 microseconds for the RS-170 video signal standard. The calculation of 242 divided by  $52.5 \times 10^{-6}$  seconds yields 4.6 MHz, the proposed limit for the video input.

The bandwidth limited signal is then converted from analog to digital form, using a flash analog to digital (A/D) converter 101 running at approximately 18 MSPS (megasamples per second), gated to run only during the active line time. This converts the 484 points per line of the input scan line sample to 1024 digital samples of the data on this line. Each digitized scan line sample is stored into a memory 103, with 240 to 242 scan line samples being digitized and stored for each field of input data.

In the preferred embodiment, the memory 103 used for storage of the input samples is a barrel shifted memory, with each field typically being stored separately. After the first and second fields have been stored, the third field is stored while the first two fields are read-out in a ping-pong fashion. The first field is then replaced by the fourth field, while the second and third are read out. Thus, all of the data will be read out each 1/60th of a second, with half of the data being updated each read-out. The

-5-

LCD flat panel display is driven in a 60 Hz, non-interlaced fashion, while the input is 30 Hz, 2:1 interlaced.

In the preferred embodiment, 20 bits are used to address the memory by the read/write address generator 105, with 10 bits defining the memory location of each sample in a scan line, 8 bits providing scan line number addresses, and the remaining two bits being used modulo 3 to define the barrel position to be written.

The image reconstruction engine 107 in the preferred analog design is simple in concept as illustrated by Fig. 2. As the LCD flat panel is rotated by 90°, the LCD flat panel driver signal data is scanned out of the barrel shifted memory as 1024 scan lines of 484 samples each. In order to reconstruct the image and display it on the LCD flat panel, the data stream preferably undergoes a fast D/A conversion 109 and is low pass filtered 111 to a level consistent with the desired display performance.

In order to determine the output bandwidth limit, the spatial frequency content and the available driving time must once again be considered. The desired spatial frequency in the 90° rotated axis is again 484 points per screen, or 242 cycles. The time available to each vertical column is found from the requirement to drive 1024 columns per frame at 60 frames per second. This time value is given by  $1 / (1024 \times 60)$  or 16.3 microseconds. Dividing 242 cycles per slit by 16.3 microseconds available gives a bandwidth of 14.9 MHz. The reconstructed vertical samples can therefore be filtered to below 15 MHz with no loss in fidelity. It will also be noted that the D/A process has its own set of bandwidth limitations, and that it is the composite of the conversion and an external low-pass filter in which it is desirable to have a flat response in low frequency and roll-off to substantially 3 dB at a frequency of substantially 15 MHz.

Finally, the bandwidth limited vertical column sample is preferably further sampled into 1024 dot samples by the A/D sampler 113. It may also be desirable at this point to take advantage of the panel design to reduce the data rates and clock speeds, although this is not essential to the inventive aspect of the present invention. The LCD flat panel can only display one of the three RGB primary colors at any sample point of the 1024 dot samples. Thus, a 3-phase 21.3 MHz clock can be used to drive the A/D sampler 113, giving correct samples of the data for the location to be displayed. The sample is truncated to 5 bits corresponding to the number of intensity levels that can be displayed by the LCD flat panel of the preferred embodiment, but it will be recognized

look-up table 115 to 7 bits for the panel data, with the last bit being obtained by a complementing operation required to change display polarity.

5           The data now consists of three serial streams of 8 bits of video data. This is typically multiplexed to 16 parallel streams for transmission to the display module. For each point, only one of the three inputs are selected by the color demux (1 to 3 demultiplexer) 117 to be passed along to the FIFO delay lines 119 which provide for a single serial (1 to 3 demultiplexer) to 16 parallel data paths, each 8 bits wide. The FIFO  
10   119 input clocks run at 64 MHz, whereas the output data is clocked to the display at 4 MHz.

          This invention has been described herein in considerable detail in order to provide those skilled in the art with the information needed to apply the novel principles and to construct and use such specialized components as are required. However, it is to  
15   be understood that the invention can be carried out by specifically different equipment and devices, and that various modifications, both as to the equipment details and operating procedures, can be accomplished without departing from the scope of the invention itself.

          The present invention is to be limited only in accordance with the scope of the  
20   appended claims, since others skilled in the art may devise other embodiments still within the limits of the claims.



CLAIMS

1. A video interface apparatus for converting an incoming interlaced video signal to an outgoing non-interlaced video signal for an LCD flat panel with an arbitrary number of rows and columns, the apparatus comprising:
  - 5 (a) analog to digital (A/D) means (101) for converting the incoming analog video signal into a corresponding digital signal;
  - (b) memory means (103) connected to the A/D means (101) for storing and outputting a plurality of rows of the digital signal;
  - (c) read and write (R/W) address generator means (105) connected to the  
10 memory means (103) for generating addresses for reading and writing data from and into the memory means; and
  - (d) image reconstruction means (107) connected to the memory means (103) for reconstructing the digital signal into an image for display on the LCD flat panel.
- 15 2. The video interface apparatus of claim 1, wherein the memory means (103) comprises barrel shifted memory.
3. The video interface apparatus of claim 1, wherein:
  - 20 (a) the incoming video signal comprises a color video signal having red, green, and blue (RGB) components; and
  - (b) the A/D means (101), memory means (103), R/W address generator means (105), and image reconstruction means (107) are duplicated in triplicate to process the RGB components of the incoming color video signal.
- 25 4. The video interface apparatus of claim 1, wherein the image reconstruction means (107) further comprises:
  - (a) digital to analog converter (DAC) means (109) connected to the memory means (103) for converting the digital signal output from the memory means to a corresponding analog signal;
  - 30 (b) line filtering means (111) connected to the DAC means (109) for filtering the analog signal to provide a smoothly varying analog signal;

-8-

- (c) second A/D means (113) connected to the line filtering means (111) for converting the smoothly varying analog signal into a corresponding LCD digital signal matching the display resolution of the LCD flat panel;
- (d) luminance correction means (115) connected to the second A/D means (113) for correcting the luminance of the LCD digital signal;
- (e) sequential read means (117) connected to the luminance correction means (115) for sequentially reading and outputting the corrected LCD digital signal; and
- (f) output memory means (119) connected to the sequential read means (117) for storing a row of the LCD digital signal and outputting the row to the LCD flat panel.
5. The video interface apparatus of claim 4, wherein the line filtering means (111) comprises a low pass filter (LPF).
6. The video interface apparatus of claim 4, wherein the luminance correction means (115) comprises a look-up table.
7. The video interface apparatus of claim 4, wherein the sequential read means (117) comprises a demultiplexer.
8. The video interface apparatus of claim 4, wherein the output memory means (119) comprises first-in first-out (FIFO) memory.
9. The video interface apparatus of claim 4, wherein the DAC means (109), line filtering means (111), second A/D means (113), luminance correction means (115), sequential read means (117), and output means (119) are duplicated in triplicate to process the RGB components of an incoming color video signal.
10. A video interface apparatus for converting an incoming interlaced video signal to an outgoing non-interlaced video signal for an LCD flat panel with an arbitrary number of rows and columns, the apparatus comprising:

- (a) first A/D means (101) for converting the incoming analog video signal into a corresponding digital signal;
- (b) memory means (103) connected to the first A/D means (101) for storing and outputting a plurality of rows of the digital signal;
- 5 (c) R/W address generator means (105) connected to the memory means (103) for generating addresses for reading and writing data from and into the memory means;
- (d) DAC means (109) connected to the memory means (103) for converting the digital signal output from the memory means to a corresponding analog signal;
- 10 (e) line filtering means (111) connected to the DAC means (109) for filtering the analog signal to provide a smoothly varying analog signal;
- (f) second A/D means (113) connected to the line filtering means (111) for converting each the smoothly varying analog signal into a corresponding LCD digital signal matching the display resolution of the LCD flat panel;
- 15 (g) luminance correction means (115) connected to the second A/D means (113) for correcting the luminance of the LCD digital signal;
- (h) sequential read means (117) connected to the luminance correction means (115) for sequentially reading and outputting the corrected LCD digital signal; and
- 20 (i) output memory means (119) connected to the sequential read means (117) for storing a row of the LCD digital signal and outputting the row to the LCD flat panel.
11. The video interface apparatus of claim 10, wherein the memory means (103) comprises barrel shifted memory.
- 25
12. The video interface apparatus of claim 10, wherein the line filtering means (111) comprises a LPF.
13. The video interface apparatus of claim 10, wherein the luminance correction means (115) comprises a look-up table.
- 30

14. The video interface apparatus of claim 10, wherein the sequential read means (117) comprises a demultiplexer.

5 15. The video interface apparatus of claim 10, wherein the output memory means (119) comprises FIFO memory.

16. The video interface apparatus of claim 10, wherein:

(a) the incoming video signal comprises a color video signal having red, green, and blue (RGB) components; and

10 (b) the first A/D means (101), memory means (103), R/W address generator means (105), DAC means (109), line filtering means (111), second A/D means (113), luminance correction means (115), sequential read means (117), and output means (119) are duplicated in triplicate to process the RGB components of the incoming color video signal.

15

17. A video interface apparatus for converting an incoming interlaced video signal to an outgoing non-interlaced video signal for an LCD flat panel with an arbitrary number of rows and columns, the apparatus comprising:

20 (a) first A/D means (101) for converting the incoming analog video signal into a corresponding digital signal;

(b) barrel shifted memory means (103) connected to the first A/D means (101) for storing and outputting a plurality of rows of the digital signal;

25 (c) R/W address generator means (105) connected to the barrel shifted memory means (103) for generating addresses for reading and writing data from and into the barrel shifted memory means;

(d) DAC means (109) connected to the barrel shifted memory means (103) for converting the digital signal output from the barrel shifted memory means (103) to a corresponding analog signal;

30 (e) LPF means (111) connected to the DAC means (109) for filtering the analog signal to provide a smoothly varying analog signal;

-11-

(f) second A/D means (113) connected to the LPF means (111) for converting the smoothly varying analog signal into a corresponding LCD digital signal matching the display resolution of the LCD flat panel;

5 (g) luminance correction means (115) connected to the second A/D means (113) for correcting the luminance of the LCD digital signal;

(h) demultiplexer means (117) connected to the luminance correction means (105) for sequentially reading the corrected LCD digital signal; and

(i) FIFO memory means (119) connected to the demultiplexer means (117) for storing a row of the LCD digital signal and outputting the row to the LCD flat panel.  
10


18. The video interface apparatus of claim 17, wherein the luminance correction means (115) comprises a look-up table.

19. The video interface apparatus of claim 17, wherein:

15 (a) the incoming video signal comprises a color video signal having red, green, and blue (RGB) components; and

(b) the first A/D means (101), barrel shifted memory means (103), R/W address generator means (105), DAC means (109), LPF means (111), second A/D means (113), luminance correction means (115), demultiplexer means (117), and FIFO memory  
20 means (119) are duplicated in triplicate to process the RGB components of the incoming color video signal.

1 / 3

*Fig. 1*

2 / 3




Fig. 2




Fig. 3



## INTERNATIONAL SEARCH REPORT

International Application No  
PCT/US 94/09475

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 G09G3/36 G06F3/147 H04N5/44 H04N5/907

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 G09G G06F H04N

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X Y A	EP,A,0 462 396 (IBM CO.) 27 December 1991 see Abstract see claims 1-3; figure 2 see column 3, line 1 - line 15 ---	1,2 3 10,17
X A	EP,A,0 291 252 (SEIKO EPSON CO.) 17 November 1988 see Abstract see figure 1 ---	1 10,17
Y A	EP,A,0 350 234 (SONY CO.) 10 January 1990 see Abstract see column 3, line 37 - column 6, line 7; figure 1 ---	3 9,16,19
A	EP,A,0 262 647 (K.K.TOSHIBA) 6 April 1988 see column 6, line 32 - column 7, line 4; figure 9 --- -/-	4,10,17

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

## \* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- "&" document member of the same patent family

Date of the actual completion of the international search

12 December 1994

Date of mailing of the international search report

16.12.94

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax (+31-70) 340-3016

Authorized officer

Corsi, F

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP,A,0 241 284 (RCA CO.) 14 October 1987  see Abstract see column 4, line 2 - line 44; figure 1 ---	4,5,10, 12,17
A	IBM TECHNICAL DISCLOSURE BULLETIN., vol.35, no.7, December 1992, NEW YORK US pages 173 - 182 'Liquid Crystal Display Gray Scale Method using a Pseudo Linear Algorithm' see the whole article -----	4,6,10, 13,17,18

## INTERNATIONAL SEARCH REPORT

Information on patent family members

Int. Appl. No.

PCT/US 94/09475

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP-A-0462396	27-12-91	US-A- 5291275	01-03-94
		CA-A- 2043177	21-12-91
		CN-A- 1063592	12-08-92
		JP-A- 4233592	21-08-92
-----			
EP-A-0291252	17-11-88	JP-A- 63280581	17-11-88
		JP-A- 63290084	28-11-88
		JP-A- 1024298	26-01-89
		JP-A- 1090680	07-04-89
		US-A- 4908710	13-03-90
-----			
EP-A-0350234	10-01-90	JP-A- 2016881	19-01-90
		DE-D- 68910596	16-12-93
		DE-T- 68910596	03-03-94
		US-A- 4935815	19-06-90
-----			
EP-A-0262647	06-04-88	JP-A- 63086932	18-04-88
		US-A- 4870661	26-09-89
-----			
EP-A-0241284	14-10-87	DE-A- 3783255	11-02-93
		DE-D- 3789396	28-04-94
		DE-T- 3789396	10-11-94
		EP-A- 0242123	21-10-87
		US-A- 4701793	20-10-87
		US-A- 4737691	12-04-88
-----			

***This Page Blank (uspto)***

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**

This Page Blank (uspto)